

Mood Board 150 变脸150


产品规格 Specification:

输入电压: AC100-240V, 输出12VDC, PF>0.7
 额定功率: 300W (25°C典型满载瞬时功率224W)
 光学效果: 线性成像光路, 多图案盘, 可旋转图案投射, 可定制单色和多色玻璃图案盘
 光源亮度: 1颗150W COB白光LED, 28A驱动, 标准7520流明输出, 整灯发光效能>36lm/W.
 光源色温: 标准6000K, 显色指数>85, 可定制色温, 定制GOBO片可自带颜色
 光场(10%)角: 标配全范围15° -40° 成像, 内置步进电机变焦和精准对焦
 控制信号: 符合WH/T 32-2008 DMX512-A标准, Arm内核MCU输出32位精度调光, PWM>1.5KHz, 摄像无频闪控制模式: 自走/主从模式, DMX通道9CH
 信号接口: 符合舞台使用IP65标准3XLR或5XLR公母头
 调光曲线: 内置Dim0-Dim4 5种调光曲线, 低DMX数值调光平滑
 频闪: 使用PWM开关LED频闪快门0-20Hz
 显示: LED显示可自动关闭, 自动显示DMX信号正常与否
 外壳材料: 拉伸铝及压铸铝ADC12, 阳极氧化及哑光喷粉黑色
 安规等级: 电气II级, 输入3*2.5mm2 黑色橡胶线(VDE, CCC), 防火V-1, 防护IP65. 配备透气阀平衡内外气压
 工作温度: -20~+45°C, 外壳最高温度60°C@25°C环境下
 认证类别: 产品通过CE, Rohs, 电源通过CQC, UL60950, UL8750等
 绝缘参数: 抗电强度1.5KV, 阻抗强度 > 2 MΩ
 净重: 12.7KG, 含4mm厚度折弯钣金双支撑架
 尺寸: 433*310*421mm(水平向前照射)

Voltage input: AC100-240V, Output 12VDC, PF>0.7
 Rated Power: 300W (224W@25°C Peak output)
 Optical Technology: Linear Image, Multi and rotating GOBOs, customized multi color GOBO
 LED Lumens: 1pcs* COB LED 28A Driving, total 7520 Lumens, Light Efficacy >36lm/W.
 LED CCT: Standard 6000K, Ra>85, could customized other CCT while Gobo have their own color
 Field Angle(10%): Comprehensive 15° -40° for Spot, Step motor adjustable. Control signal: E1.11 - 2004 USITT DMX512-A, 32 bit ARM MCU, PWM>1.5KHz, Video flicker free.
 Control mode: stand alone/master and slave, DMX 9CH
 Signal connector: Canon 3XLR/Canon 5XLR IP65
 Dimming Curve: Dim 4 square law dimming, smooth in low DMX Value dimming, not Jumping, no vision shock
 Strobe: With PWM shutter, 0-20Hz flash speed.
 Display: LED display, auto turn off after 2 minutes no operation, auto show DMX signal situation. Housing material: Extrusion 6063 and Die cast ADC12, Anodized and Painted Matte black.
 Safty: Class II, 3C 2.5mm2 VDE cable, Flame Rating V-1, Protect Rated IP65 with Vent.
 Operate temperature: -20~+45°C, Lamp body peak temperature 60°C@25°C Environment. Certificated: Product pass CE, Rohs, SMPS pass CQC or UL60950, UL8750.
 Insulated: Dielectric strength 1.5KV, Impedance strength > 2MΩ
 Weight: 12.7KG, with double yokes 4mm thick supporting bracket.
 Size: 433*310*421mm (Horizontal spot direction)

产品特点 Features:

一个固定图案盘, 一个旋转图案盘, 每只7色片, 其中一只空白出正白
 BOBO片出光直径28mm, 可单色, 可多色定制GOGO片
 标准内置8棱镜和雾化镜, 可选3棱镜
 内置图案方向调整和旋转, 速度可变
 标配15° -40° 光斑, 内置步进电机调焦, 和精准对焦
 使用雾化镜柔光投射光斑为35° -60°
 DMX512信号控制, 自走、主从机控制, 多机互联控制, led显示屏
 LED显示可自动关闭, 自动显示DMX信号正常与否
 内置Dim4曲线调光从0-100%, 调光频率1.5KHz, 拍照无闪烁
 内置温度控制功能, 当LED工作过热时, 智能降低LED的输出功率, 15000小时产品寿命
 配备透气阀, 内外气压平衡, 玻璃面内部变热时无雾气
 1 fixed Gobo wheel and one rotating gobo wheel both including 7 gobos and one empty to offer white color.
 Gobos 28mm hole for lights to go through, single or multi-color, customized GOGOs.
 Built-in one 8-facets Prism and one Frosted Lens
 Built-in MOTO to adjust GOBO direction, and rotatable.
 15° -40° Beam Angle Available by motorized Zoom and fine focusing.
 Frosted output field Angle 35° -60°
 DMX512 signal control, with LED screen for setting.
 Lumiled LED, 7520 Lumens Output, Low consume, stable performance, long longevity.
 Display could auto turn off after 2Minutes no operation, show DMX signal situation.
 Dim 4 Square law dimming, video flicker free.
 NTC temperature control system inside, reduce the power output when LED working temperature is too high.
 With waterproof air vent to balance pressure, get rid of moisture on glass innerface.



优点

- 使用线性光学成像技术, 内置变焦、精准对焦及雾化
- 适用于小剧本型投射, 可以为动态连续的脚步, 快速切换
- 清晰的成像光斑, 提供cdr文件格式图案需求可快速定制图案
- Mood board是指经由对使用对象与产品认知的色彩, 影像, 数字资产或其它材料的收集, 可以引起某些情绪反应, 作为设计方向与形式的参考。

The Face Off Series

变脸系列

Mood Board 150 变脸150

