

Proverbs R200UV 箴言R200UV

产品规格 Specification:

输入电压: AC 90-240V 47-63Hz, PF:>0.9
 输出电压: DC24V, 15000小时开关电源使用寿命
 额定功率: 90W (@220V 50Hz)
 灯具效率: >0.9, 整灯发光效能>300mW/W辐射量
 光源亮度: 36颗*3W Helio UV光LED, 620mA驱动, 总27W辐射功率输出, 约11流明。
 光源波长: 380-405nm
 光场 (10%) 角: 标准30°, 8°、15°、45°、60°、60*1° 等可选
 控制信号: DMX512, 32位精度调光, 低DMX数值调光柔滑, 无跳闪, 无视觉冲击
 控制模式: 自走/主从模式
 通道数: DMX控制, 标准3通道, 调光加频闪加调光曲线
 调光: 内置Dim0-Dim4 5种调光曲线, PWM>1500Hz, 摄像无频闪
 外壳材料: 压铸铝ADC12, 标准哑光黑色, 可定制喷漆白色, 配备挡光板
 安规等级: 电气II级, 输入3*2.5mm2 黑色橡胶线(VDE, CCC), 防火V-1, 防护IP65
 工作温度: -20~+45°C, 铝基板最高温度80°C
 认证类别: 产品通过CE, Rohs, 电源通过CQC, UL60950, UL8750等
 净重: 4.7Kg, 含3mm厚度折弯钣金双支撑架
 尺寸: 30*32*39CM

Voltage input: AC 90-240V 47-63Hz, PF>0.9
 Volatage Output: 24V, SMPS longevity 15000Hours
 Rated Power: 90W (@220V 50Hz)
 Luminaire Efficiency: >0.9, Light Effiacy >300mW/W.
 LED Lumens: 36pcs *3W Helio UV LED, total 27W Radiometric Power, about 11 Lumens.
 LED Wavelength: 380-405nm.
 Field Angle(10%): standard 30°、8°、15°、45°、60°、60*1° Etc optional.
 PWM frequency: >1500Hz, video flicker free
 Control signal: DMX512, 32 bit Dim 4 square law dimming, smooth in low DMX Value dimming, not Jumping, no vision shock
 Control mode: DMX1990/DMX512A/stand alone/master and slave
 Chanel option: 3CH, Dimmer, Strobe and Dimming Curve.
 Housing material: Die cast aluminum ADC12, standard Matte balck, customized glossy White painting, barndoor available.
 Safty: Class II, 3C 2.5mm2 VDE cable, Flame Rating V-1, Protect Rated IP65.
 Operate temperature: -20~+45°C, Light board peak temperature 80°C
 Certificated: Product pass CE, Rohs, SMPS pass CQC or UL60950, UL8750.
 Weight: 4.7Kg, with double yokes 3mm thick supporting bracket.
 Size: 30*32*39CM

产品特点 Features:

27W高能波长黑光辐射输出, 精准配光, 10%光场角内流明数量占比90%以上
 远程投射能量, 为建筑物中荧光物质, 环境不饱和碳链聚合物提供能量;
 可为设计师推荐荧光粉调配方案, 以及建筑表面隐形彩绘解决方案, 使用寿命3年以上
 适用于不方便安装灯具而需要特殊发光的位置, 尤其为高亮度荧光。
 DMX512信号控制, 自走、主从机控制, 多机互联控制, 4按钮地址码设置led显示屏
 内置Dim4曲线调光从0-100%, 调光频率1500Hz, 拍照无闪烁, 内置频闪模式、渐变等效果
 每个LED回路使用恒流和PWM调光, 保证LED电流不超载
 内置温度检测功能, 当LED工作过热时, 智能降低LED的输出功率。
 光束角 (10%强度) 标准30度, 可选配其他角度, 以及扩散片和60*1° 三次配光片。
 压铸模具, 坚固耐用, LED灯头散热充分, 热隔离式驱动安装, 开关电源和主板高达15000小时的使用寿命。
 配备透气阀, 内外气压平衡, 玻璃面内部变热时无雾气
 27W Radiometric Power Output, high efficiency light output 90% Lumens within 10% Intensity field angle.
 Project energy to place not easy install lights, for architecture, Organic essence with C=C train.
 Offer recommended paiting powder mixing solutions and 3 years last invisible colorfull paiting solutions
 DMX512 signal control, 4 buttons address setting with LED screen, also Master and Slave.
 Dim 4 Square law dimming for 0-100%, video flicker free, with strobe/gradual change inbuilt programs;
 Independent circuit driving, each 620mA, even ampere distribute.
 NTC temperature control system inside, MCU reduce the power output when LED working temperature is too high;
 Field Angle standard 30°, could choose other angle, and also frosted piece and 60*1° third optical piece.
 Strong die cast body enough for LED heatsink, seperated driving Part design make sure more than 15000 Hours Longevity for SMPS and Main board.
 With waterproof air valve to balance pressure, get rid of mosuisture on glass innerface.

优点

- 防水黑光灯, 提供隐形艺术彩绘方案
- 建议用于外墙表面, 或建筑细部精确照明
- 可与一般照明方案叠加, 使用控制系统进行场景切换
- 可用于高反射表面打光, 解决以往传统灯具缺陷
- 多种配光方案可选



The Painting Series 丹青系列 Proverbs R200UV 箴言R200UV

